

SHEET PRODUCTION CAPABILITIES

Max.Width	Min.Width	Max.Thickness	Min. Thickness	Embossing
1200-1650	600-800	0.4	0.33	Sand/Orange
1650	600	0.5	0.40	
1650	400	2.0	0.50	
1200-1650	600-800	0.4	0.33	Sand/Sand
1650	600	0.5	0.40	
1650	400	2.0	0.50	
1200-1650	600-800	0.4	0.35	Sand/Gloss
1650	600	0.5	0.40	
1650	400	2.0	0.50	
1200-1650	600-800	0.4	0.35	Gloss/Orange
1650	600	0.5	0.40	
1650	400	2.0	0.50	
1120	900	0.4	0.20	Sand/Pix
1120	900	0.4	0.20	Sand/Matt
1120	900	0.4	0.20	Sand/Leather
1120	900	0.4	0.20	Sand/Walnut
640	400	1.5	0.50	Gloss/Diagonal
1300	800	1.5	0.50	
1020	800	0.4	0.30	Gloss/Gloss
820	600	1.2	0.40	
1500	1200	1.2	0.40	
1120	900	0.4	0.20	Gloss/Pix
640	400	2.0	0.40	Duatone/Orange
1300	800	2.0	0.40	
640	400	2.0	0.40	Duatone/Gloss
1300	800	2.0	0.40	
640	400	2.0	0.40	Sand/Dots
1300	800	2.0	0.40	
1020	800	0.4	0.35	Satin/Sand
1650	1200	1.5	0.40	
1020	800	0.4	0.35	Satin/Gloss
1650	1200	1.5	0.40	

Thickness tolerance: +0.01/-0.03mm

In-Line tolerance: size of sheet -0/+5mm

Angular tolerance: +/-0.2 degree